

VT-10

Vision Tester



* Not available for sale in the United States.
 * Not available in all countries, please check with your distributor for availability in your country
 * Subject to change in design and/or specifications without advanced notice.

IMPORTANT In order to obtain the best results with this instrument, please be sure to review all user instructions prior to operation.



TOPCON CORPORATION
 75-1 Hasunuma-cho, Itabashi-ku, Tokyo 174-8580, Japan. Phone:+81-(0)3-3558-2522/2502 Fax:+81-(0)3-3965-6898 www.topcon.co.jp

TOPCON MEDICAL SYSTEMS, INC.
 111 Bauer Drive, Oakland, NJ 07436, U.S.A.
 Phone:+1-201-599-5100 Fax:+1-201-599-5250 www.topconmedical.com

TOPCON CANADA INC.
 110 Provencher Avenue, Boisbriand, QC J7G 1N1 CANADA
 Phone:+1-450-430-7771 Fax:+1-450-430-6457 www.topcon.ca

TOPCON EUROPE MEDICAL B.V.
 Essebaan 11, 2906 LJ Capelle a/d IJssel, P.O. Box 145,
 2900 AC Capelle a/d IJssel, THE NETHERLANDS
 Phone:+31-(0)10-4585077 Fax:+31-(0)10-4585045
 E-mail: medical@topcon.eu; www.topcon-medical.eu

ITALY OFFICE
 Viale dell'Industria 60, 20037 Paderno Dugnano, (Milano), ITALY
 Phone:+39-02-9186671 Fax:+39-02-91081091 E-mail: info@topcon.it; www.topcon.it

DANMARK OFFICE
 Praestemarksvej 25, 4000 Roskilde, DANMARK
 Phone:+45-46-327500 Fax:+45-46-327555
 E-mail: topcon@topcondanmark.dk www.topcondanmark.dk

IRELAND OFFICE
 Unit 276, Blanchardstown, Corporate Park 2 Ballycoolin Dublin 15, IRELAND
 Phone:+353-18975900 Fax:+353-18293915 E-mail: medical@topcon.ie; www.topcon.ie

TOPCON S.A.R.L.
 BAT A1 3 route de la rovette 93206 SAINT DENIS CEDEX
 Phone:+33-1-49-21-23-23 Fax:+33-1-49-21-23-24 E-mail:topcon@topcon.fr; www.topcon.fr

TOPCON DEUTSCHLAND MEDICAL G.m.b.H.
 Hanns-Martin-Schleyer Strasse 41, D-47877 Willich, GERMANY
 Phone:+49-(0)2154-8850 Fax:+49-(0)2154-885177 E-mail:med@topcon.de; www.topcon.de

TOPCON SCANDINAVIA A.B.
 Neorgatan 2, P.O. Box 25, 43151 Mölndal, SWEDEN
 Phone:+46-(0)31-7109200 Fax:+46-(0)31-7109249 E-mail:medical@topcon.se; www.topcon.se

TOPCON ESPAÑA S.A.
 HEAD OFFICE
 Frederic Montpou 4 Esc. A Bajos 3, 08960 Sant Just Desvern Barcelona, SPAIN
 Phone:+34-93-4734057 Fax:+34-93-4733932 E-mail: medical@topcon.es; www.topcon.es

TOPCON (GREAT BRITAIN) LTD.
 Topcon House, Kennet Side, Bone Lane, Newbury, Berkshire RG14 5PX United Kingdom
 Phone:+44-(0)1635-551120 Fax:+44-(0)1635-551170 E-mail:medical@topcon.co.uk; www.topcon.co.uk

TOPCON POLSKA Sp. z o. o.
 ul. Warszawska 23, 42-470 Siewierz, POLAND
 Phone:+48-(0)32-6705045 Fax:+48-(0)32-6713405 www.topcon-polska.pl

TOPCON SINGAPORE MEDICAL PTE. LTD.
 1 JALAN KILANG TIMOR #09-01 PACIFIC TECH CENTRE SINGAPORE 159303
 Phone:+65-68720606 Fax:+65-67736150
 E-mail:medical_sales@topcon.com.sg www.topcon.com.sg

REPRESENTATIVE OFFICE IN INDONESIA
 Level 38, Tower A, Kota Kasablanka unit GH-04, Jl.
 Casablanca, Kav 88, Jakarta, Indonesia 12870
 Phone:+62-21-2963-8004

TOPCON INSTRUMENTS (MALAYSIA) SDN.BHD.
 No. D1, (Ground Floor), Jalan Excella 2, Off Jalan Ampang Putra,
 Taman Ampang Hill, 55100 Kuala Lumpur, MALAYSIA
 Phone:+60-(0)3-42709866 Fax:+60-(0)3-42709766

TOPCON INSTRUMENTS (THAILAND) CO.,LTD.
 77/62 Sinsathorn Tower, 37th Floor, Krungthornburi Rd., Klongtonnai,
 Klongsarn, Bangkok 10600, THAILAND
 Phone:+66(0)2-440-1152-7 Fax:+66-(0)2-440-1158

Mehra Eyetech Private Limited
 801 B Wing, Lotus Corporate Park, Graham Firth Steel Compound Goregaon (East)
 Mumbai 400063 Maharashtra, INDIA
 Phone:+91-22-61285455 www.mehraeyetech.in

PRINTED WITH SOY INK
 © 2000-2016 TOPCON CORPORATION All Rights Reserved
 Printed in Japan 2010 05-30 NP E051-3 TMS · TS · AS



YOUR VISION. OUR FOCUS.

Versatility & Convenience Combined with Unparalleled Response & Precision

Precision and convenience are a tradition in high quality TOPCON optical instruments. The VT-10 vision tester advances this tradition still further, making refraction quicker and easier than ever before, providing unequaled performance and exceptional versatility. Precision in design and workmanship guarantees accuracy in refraction measurements—accuracy that won't deteriorate even after long years of use. Total quality from TOPCON means you can have total confidence in the performance you'll enjoy from the VT-10 vision tester.



VT-10
Vision Tester

A Half-Century of Dedication to Superior Optical Instrumentation

TOPCON has remained a leader and major innovator in optical instrumentation and technology for more than half a century. Intensive dedication to engineering research and manufacturing precision has made TOPCON the name to know for reliable performance.

Precision Engineering for Superior Performance;

Designed for total precision, the VT-10 vision tester represents TOPCON optical engineering at its very best—extreme accuracy over the widest possible testing range. Internal mechanisms are precisely machined to the finest tolerances; parts and components are made from the finest materials, all corrosion-resistant and tested for performance and durability.

Multi-Coated Lenses for Superior Optical Performance

Every lens used in the VT-10 receives a special multi-coating that eliminates flare, ghost images and reflections. In addition, the multi-coating assures clearer, brighter images with improved contrast and excellent color fidelity.



The TOPCON VT-10 is available in either black or gray finishes.

Controls & Scales Designed to Make Refraction Quick & Comfortable; Features for Functional Versatility



Wide Testing Range

The testing range available with the VT-10 is extraordinary, the standard cylinder power range extends to 6.00D in 0.25D increments. In addition, auxiliary lens sets are incorporated to fine-tune cylinder power measurements to 0.12D increments or extend cylinder power range to 8.00D. Accurate prism reading even below 0.5Δ are possible thanks to the 20Δ range (1Δ increments) of the precision-gear rotary prism loupes. The VT-10 is also available in plus or minus cylinder models.



Synchronized Cross-Cylinders

The most significant time-saving feature of the VT-10 is its synchronization of cross-cylinder loupe rotation to cylinder axis adjustment. Special gearing automatically synchronizes the rotation of the loupe each time you change cylinder axis correction. The result? You simply read a single scale, one time, after completing a full series of axis checks. The bi-loupe turret lets you index power or axis loupes with a single touch.



Easy Controls & Clear Scales

Control of cylinder axis and power testing is amazingly simple; concentric control knobs within a double-calibration axis scale make adjustment a quick, one hand action through the full 360° range. The axis scale reads in 5° increments, with 15° markings. An additional axis scale is located at the main aperture, for convenient reference during retinoscopy. The low position of the control knobs keeps the operator's hands out of the line of vision.



Versatile Adjustments

Convenient dual controls make it easy for the operator to adjust interpupillary distance, in a range from 48mm to 75mm. The mechanism is sealed for protection and smooth functioning. An easy-to-read scale provides 1mm graduations, and a vergence adjustment controls reductions in P.D. during near testing.



A Wide Range of Versatile Auxiliary Lenses

The TOPCON VT-10 comes with a full complement of versatile auxiliary lenses—10 different lenses plus two open apertures, any of which can be indexed into position with one-touch speed and convenience. A red lens/green lens shift, for example, is immediately available for binocular vision testing. The auxiliary lens plate has a flat black finish to prevent stray reflections during use.



Fast, Precise Results

TOPCON VT-10 incorporates a single-dial power control that lets the operator quickly dial in any spherical power from +16.75D through 0 to -19.00D, in 0.25D increments. To make settings faster, a strong sphere control allows adjustment in 3.00D steps; the auxiliary lens knob provides for fine-tuning in 0.12D increments for absolute accuracy.




Other Features

Simple Convergence System

Precise measurements at both near and distant testing for optimal results.



One quick adjustment of the dual convergence levers and the VT-10 provide total accuracy in near vision testing measurement.



Sealed Optics

The examination apertures feature cover lenses for convenience and protection. Dust, eyelashes, etc. can't get in, and the lenses are easily removed for simple cleaning. The patient always has a bright, clear image to view. (Standard accessories include face shields that can be sterilized for optimum comfort and hygiene.)



Accessories

The holder for rotary near point card mounts to a sturdy rod with a distance scale from 5 to 28 inches—centimeter and diopter scales are included. A hinged bracket moves it into position immediately, or raises it out of the way. Accessory lenses come in an accessory box, holding dual sets or -0.12D and -2.00D cylinder lenses.



Specifications

Type Subjective refraction testing equipment

Item and range of measurement The value in () is with accessory lens or auxiliary lens attached:

Myopia	0 to -19.00D in 0.25D step (0.12D step)
Hyperopia	0 to +16.75D in 0.25D step (0.12D step)
Astigmatism	0 to -6.00D (-8.00D) in 0.25D step (0.12D step)
Cross-Cylinder	± 0.25D (± 0.37D and ± 0.50D as option)
Phoria and vergency	20△ to 0 to 20△ by 1△ step Inner 40△ Outer 40△ (50△) Upward and Downward 40△ (46△)
Near vision test	Main optical axes of both lenses converges by means of a tilt mechanism at 40cm in front of the eyes at 64mm P.D. If P.D. for far vision is less than 54mm, converging operation stops.
Binocular balance test	Rotary prism and polarizing lens methods are available.
P.D.	48 to 75mm by 1mm step
Level adjustment	More than 4.5° for right and left banks
Dimensions	335 (at 64mm P.D. setting) x 97 x 294mm
Weight	4.5kg

Content of Auxiliary Lens Dial:

"O /O"	Open Aperture
"R"	Retinoscopic Lens: +1.50D standard +2.00D option
"P"	Polarizing Filter
"WMV/RMV"	Maddox Rod, vertical: white (left) red (right)
"WMH/RMH"	Maddox Rod, horizontal: white (left) red (right)
"GL"	Green Lens (left)
"RL"	Red Lens (right)
" +.12"	+0.12D Spherical
"PH"	Pin Hole
"10 I"	10 Diopter Prism Base In (left)
"6 U"	6 Diopter Prism Base Up (right)
" ± .50"	± 0.50D Fixed Cross Cylinder
"OC"	Occluder

Plus and minus cylinder models available, also the choice of color—black or light grey.

Optional Accessories



± 0.37 / ± 0.50D cross cylinder, + 2.00D retinoscopic lens.